

Innlights

Displaysolutions

InnScreen C2 HE

[Pixel Pitch 2.84 mm]

// RENTAL / INDOOR

High Standards. Best Performance.
*Ultimate image experience designed for
best stage rental performance.
Automatic module calibration.
2D / 3D video processing.*

INNSCREEN FEATURES:

- / Black Face & Non Glossy LED
- / 2D & 3D video processing



Innlights

Displaysolutions

InnScreen C2 HE

PHYSICAL SPECS

Pixel Pitch [mm]	2,84
Brightness [cd/m ²]	1.000
Protection Level [Front/Back]	IP 21 / IP 43
Panel Weight [kg]	8,5
Panel Size [mm]	500 × 500 × 75
Panel Resolution [px]	176 × 176
Pixel Density [px/m ²]	123.904
Panel Material	Aluminum CNC finish

VISUAL SPECS

Viewing Angle Hor/Ver [Deg]	140 / 140
Refresh Rate Min. [Hz]	3.840
IC Driver	MBI 5253
LED Type	SMD 2020 [black face]
LED	Nationstar [gold wire]
Processing [bit]	15
Video Processing	INNVISION i9 <i>built on Colorlight</i>



INNLIGHTS STANDARDS

WEEE-Reg.-No.: DE 55860379
Certificates: TUV CE, EMC CE (EMV)

POWER

Voltage [V]	100 - 220
Power Cons. Max./Avg. [W/Panel]	184 / 74
Power Cons. Max./Avg. [W/m ²]	736 / 296

ENVIRONMENT

Operating Humidity [RH]	10% ~ 90%
Operating Temp. Min./Max. [°C]	-20 / +60