

Innlights

Displaysolutions

InnScreen T3 **MINI**

[Pixel Pitch 3.91×7.81 mm]

// TRANSPARENT INDOOR & SEMI-OUTDOOR

Vivid. Translucent. Light.

Semi-transparent and wind-permeable ultra-lightweight in- and semi-outdoor screen delivering brilliant visuals and flexible design possibilities. Quick installation.

- / Immersive, vivid visuals
- / Semi-transparent
- / Ultra-lightweight
- / High contrast ratio / 6000:1

- / **Seamless flat** / 0°
- / **Concave & Convex**
 $\pm 5^\circ$ / $\pm 10^\circ$ / $\pm 15^\circ$
- / **90° corner**



Innlights

Displaysolutions

InnScreen T3 **MINI**

PHYSICAL SPECS

Pixel Pitch [mm]	3.91 × 7.81
Protection Level [Front/Back]	IP 54
Weight [kg/m²]	19,2
Panel Size [mm]	500 × 500 × 88.5
Panel Resolution [px]	128 × 64
Curving [deg]	± 5° / ± 10° / ± 15°
Minimum Radius [m/Panels]	1,92 / 24
Panel Material	Die-cast aluminum

VISUAL SPECS

Brightness [cd/m²]	2500
Viewing Angle Hor/Ver [Deg]	160 / 140
Refresh Rate Min. [Hz]	3840
IC Driver	MBI QFN5253
LED	Kinglight
LED Type	SMD 1921
Contrast Ratio	6000:1
Processing [bit]	14 - 16
Video Processing	INNVISION T6 <i>built on Colorlight</i>



SEMI
TRANSPARENT



90°
CORNER

POWER

Voltage [V]	100 - 240
Power Cons. Max./Avg. [W/m²]	400 / 200

ENVIRONMENT

Operating Humidity [RH]	10% - 90%
Operating Temp. Min./Max. [°C]	-20 / +40

INNLIGHTS STANDARDS

WEEE-Reg.-No.: DE 55860379
Certificates: TUV CE, EMC CE (EMV)