

Innlights

Displaysolutions

InnScreen X2 **Pro**

[Pixel Pitch 2.6 mm]

// Hi-Res / High Brightness / Outdoor

High-resolution. Bright. Reliable.

High-quality premium images with high brightness and reliable stability meet lightweight construction and all-weather durability. A slim, neat installation paired with high-precision assembly and efficient heat management ensures long-term performance.

- / High brightness / **5000 nits**
- / Robust protection / **IP66**
- / Exacting Precision
- / Stability & Reliability
- / Efficient Heat Management

Available:

- / **90° corner**
- / **Concave & convex curves**



Innlights

Displaysolutions

InnScreen X2 **Pro**

Physical Specs



Pixel Pitch [mm]	2.6
Protection Level [Front/Back]	IP 66
Weight [kg/m ²]	26
Panel Size [mm]	500 × 1000 × 75
Panel Resolution [px]	192 × 384
Frame Material	Aluminum

Visual Specs

Brightness [cd/m ²]	5000
Viewing Angle Hor/Ver [Deg]	140 / 140
Refresh Rate Min. [Hz]	3840
LED	Nationstar
LED Type	SMD 3in1
Color Processing Depth [bit]	14
Video Processing	InnVision T6 by Colorlight



CREATIVE SHAPES AVAILABLE



INNLIGHTS STANDARDS

WEEE-Reg.-No.: DE 55860379

Certificates: TUV CE, EMC CE (EMV)

Power

Voltage [V]	220
Wattage Avg./Max. [W /m ²]	160 / 450

Environment

Operating Humidity [RH]	10% - 90%
Operating Temp. Min./Max. [°C]	-20 / +60