

Innlights

Displaysolutions

Pop-Up Display **GOB** OUTDOOR **DOUBLE-SIDED**

[Pixel Pitch 1,875 mm]

// PORTABLE DISPLAY. TRUE-TO-LIFE IMAGE.
SEAMLESSLY CONNECTABLE.

Portable POS solution with integrated signage player. True-to-life image with seamless blending from extremely bright to ultra dark. Super high resolution and wide color gamut for vibrant colours. Ultraslim and lightweight. X-GOB coating ensures shatterproof and all-weather durability.

- / **Intelligent image processing**
- / **Excellent reliability**
- / **X-GOB + IP65**
- / **Energy-saving**
- / **Seamlessly connectable**

Plug & play media player with on-screen display and local storage.

INNSCREEN FEATURES:

- / True-to-life image
- / Super high contrast 10000:1
- / Plug & play
- / Seamless connectivity of multiple displays



Innlights

Displaysolutions

Pop-Up Display **GOB** **DOUBLE-SIDED**

PHYSICAL SPECS

Pixel Pitch [mm]	1,875
Protection Level [Front/Back]	IP 65
Weight [kg]	90
Screen Resolution [px]	288 × 1024
Screen Size [mm]	540 × 1920
Dimension [WxHxD/mm]	542.4 × 2072.2 × 500

VISUAL SPECS

Brightness [cd/m²]	4000
Viewing Angle Hor/Ver [Deg]	160 / 160
Refresh Rate Min. [Hz]	3840
Contrast Ratio	10000:1
Grayscale [bit]	14
LED	Flip-Chip

Seamless
lining up

Instant setup.
**SEAMLESS CONNECTION.
LIMITLESS SCREENS.**



CLOUD REMOTE CONTROL SYSTEM

*Global cluster management
& remote monitoring via
Windows / iOS / Android*



PLAYBACK

PC / Phone / PAD / USB

PORTS

USB / HDMI / Audio / LAN

INNLIGHTS STANDARDS

WEEE-Reg.-No.: DE 55860379

Certificates: TUV CE, EMC CE (EMV)

POWER

Voltage [V]	120 - 240
Wattage Avg./Max. [W/m²]	220 / 720

ENVIRONMENT

Operating Humidity [RH]	10% - 90%
Operating Temp. Min./Max. [°C]	-10 / +40