

Innlights

Displaysolutions

X

Kultour®

POP-UP DROP

[Pixel Pitch 3.9 mm]

// 4 m² PLUG & PLAY OUTDOOR
HIGH RESOLUTION LED-SCREEN

*High resolution outdoor POP-UP-LED-Screen
with < 15 minutes set up and supereasy playback,
portrait, landscape or three-sided.*

- / **Mobile plug & play LED-Screen
with less than 15 minutes setup**
- / **2,75 × 1,50 m**
- / **Operation and status check worldwide
via LTE connection**
- / **No on-site technician needed**
- / **Up to wind zone 3** (screen remains up)
- / **integrated Innvision video scaler**
- / **Brightness sensor**
- / **PORTRAIT / LANDSCAPE / THREE-SIDED**

OPTIONAL:

- / CCTV (video monitoring)
- / ELA (escape loudspeaker)
- / Headlight
- / Evocount sensors / connection to Evocount system

INNSCREEN FEATURES:

- / High image quality with high brightness
- / Black Face LED
- / Plug & play
- / Integrated INNVISION video scaler



SCREEN
FIRE CLASS



CERTIFIED
WIND ZONE 3

Innlights

Displaysolutions

POP-UP **DROP** 4m²

PHYSICAL SPECS

Pixel Pitch [mm]	3,9
Brightness [cd/m ²]	4.500
Protection Level [Front/Back]	IP 66
Screen Size [m]	2,75 × 1,50
Split screen width [m]	(1 × 0,75 × 1)
Height [Top Edge / m]	2,6 / 3,3 / 4
Weight [Screen/ kg]	136
Weight [Total/ t]	1,4

VISUAL SPECS

Viewing Angle Hor/Ver [Deg]	160 / 120
Refresh Rate Min. [Hz]	3.840
LED	<i>Innlights customized</i>
LED Type	SMD 1921 [black face]
Processing [bit]	15
Video Processing	INNVISION <i>built on Colorlight</i>

PORTRAIT
LANDSCAPE
THREE-SIDED



PLAYBACK
PC / Mobile



CLOUD REMOTE
Global LTE monitoring & control



PORTS
HDMI / SDI / LAN

POWER

Voltage [V]	110 - 220
Power Cons. Max./Avg. [W/m ²]	600 / 180

ENVIRONMENT

Operating Humidity [RH]	95%
Operating Temp. Min./Max. [°C]	-20 / +60

INNLIGHTS STANDARDS

WEEE-Reg.-No.: DE 55860379
Certificates: TUV CE, EMC CE (EMV)